



TECE:


OSNOVNI ELEMENTI SLIVNIKA

NASADNI DELOVI KOMPLET SA RESETKOM

Okvir za rešetku, plastika

Okvir za rešetku, inox

100 mm





3660001

3660002

3660007

150 mm



3660003

366004



3660008

IZOLACIJA

Bitumenska manžetna za izolaciju u spoju (PP/PE)

Set prirubnica za spoj stezne prirubnice (inox)

Bitumenska folija EPDM 480x480mm



3690004

3690003

3690006

TELO SLIVNIKA












	Vertikalni	Horizontalni		
DN 50				
	3601600	3601400	3601401	3601500
DN 70				
	3603600	3603500		
DN 100				
	3607600	3607500		

RESETKE

NASTAVCI

100 mm

142 mm

<p>Ulivni nastavak sa univerzalnom prirubnicom (plastika)</p>		<p>Bez srafova</p>		
<p>3660005</p>			<p>3665002</p>	
<p>Ulivni nastavak (plastika)</p>		<p>Mogucnost pricvrscivanja srafovima</p>		
<p>3660006</p>			<p>3665006</p>	
<p>DODATAK ZA SUVI SLIVNIK</p>				
<p>Zatvarac neugodnih mirisa, posebno plitak</p>		<p>Mogucnost pricvrscivanja srafovima</p>		
<p>Zatvarac neugodnih mirisa, Norm</p>			<p>3695001</p>	
<p>Dvostepeni membranski zatvarac neugodnih mirisa</p>			<p>3695002</p>	

KOMPLETNI SLIVNICI

TECEdrainpoint S 110 set ,slivnik pločki sa univerzalnom prirubnicom

- * telo slivnika DN 50 horizontalno, pločko sa univerzalnom prirubnicom
- * ucinak odvodnje 0.8 l/s
- * smanjen vodeni mlaz = 30 mm
- * sa kuglicnim zglobovima i bočnim odvodom DN 40, uključujući završne cepove
- * odvojivi dodatak za suvi slivnik
- * ulivni nastavak sa okvirom od plastike (ABS) i O-prstenom
- * TECEdrainpoint resetka od inoxa 100x100 mm



3601100

TECEdrainpoint S 130 set ,slivnik vertikalni sa univerzalnom prirubnicom

- * telo slivnika DN 50 vertikalno, sa univerzalnom prirubnicom
- * ucinak odvodnje 1.5 l/s
- * vodeni mlaz = 50 mm (DIN EN 1253)
- * odvojivi dodatak za suvi slivnik
- * ulivni nastavak sa okvirom od plastike (ABS) i O-prstenom
- * TECEdrainpoint resetka od inoxa 100x100 mm



3601300

TECEdrainpoint S 120 set ,slivnik Norm sa univerzalnom prirubnicom

- * telo slivnika DN 50 horizontalno, Norm sa univerzalnom prirubnicom
- * ucinak odvodnje 1.1 l/s
- * vodeni mlaz = 50 mm (DIN EN 1253)
- * sa kuglicnim zglobovima i bočnim odvodom DN 40, uključujući završne cepove
- * odvojivi dodatak za suvi slivnik
- * ulivni nastavak sa okvirom od plastike (ABS) i O-prstenom
- * TECEdrainpoint resetka od inoxa 100x100 mm



3601200

TECEdrainpoint S 50 set, slivnik pločki

- * telo slivnika DN 50 horizontalno, pločko sa pridržnim rubom
- * ucinak odvodnje 0.6 l/s
- * smanjeni vodeni mlaz = 30 mm
- * odvojivi dodatak za suvi slivnik
- * ulivni nastavak sa okvirom od plastike (ABS) i O-prstenom
- * TECEdrainpoint resetka od inoxa 100x100 mm



3601050