

TEMPOMATIC MIX PRO electronic mixer

Ref. 495253

Mains supply

DESCRIPTION




TEMPOMATIC MIX PRO electronic mixer - Ref. 495253

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Shock-resistant infrared presence detection sensor.
Chrome-plated solid brass body with fixing reinforced by 2 stainless steel rods.
PEX flexibles with filters and solenoid valves M3/8".
Swivelling spout with smooth interior (reduces bacterial can development).
Removable spout for cleaning.
Anti-blocking security.
Side temperature control with ergonomic LH lever and adjustable maximum temperature limiter.
Two shut-off options on 230/12V models:
- Standard mode: timed flow with automatic shut-off.

- On/Off mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow. Thermal shocks are possible.
10-year warranty.





TECHNICAL FEATURES

TEMPOMATIC MIX PRO electronic mixer - Ref. 495253

Connector	M3/8"
Technology	Electronic
Drop height	310mm
Spout length	200mm
Flow rate	4 lpm
Standards and certifications	 
Warranty	



ADVANTAGES

-  Independent IP65 electronic control unit
-  Water savings up to 85%
-  Total hygiene : no manual contact
-  Anti-bacterial proliferation duty flush

